SAFETY DATA SHEET

Date of issue/Date of revision

: 31 January 2014



SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: LEYLAND TRADE High Gloss
Product code	: 00264606
Other means of identification	: Not available.

1.2 Relevant identified use	s of the substance or mixture and uses advised against
Product use	: Consumer applications, Professional applications.
Use of the substance/ mixture	: Coating.

1.3 Details of the supplier of the safety data sheet

PPG Architectural Coatings UK Ltd Huddersfield Road Birstall, West Yorkshire WF179XA United Kingdom +44 (0) 1924 354000 Fax: +44 (0) 1924 354533

- e-mail address of person : regulatoryaffairs@ppg.com responsible for this SDS
- 1.4 Emergency telephone number

Supplier

 Telephone number
 :

 +44 (0) 1924 354000
 :

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

Classification according to Directive 1999/45/EC [DPD]

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification	: R10
	R66

Physical/chemical hazards : Flammable.

Human health hazards : Repeated exposure may cause skin dryness or cracking.

See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Conforms to Regulation (EC) No.	1907/2006 (REACH), Annex II, as amended	by Regulation (EU) No. 453/2010 -
United Kingdom (UK)		

Code : 00264606	Date of issue/Date of revision	: 31 January 2014
LEYLAND TRADE High Gloss		

SECTION 2: Hazards identification

÷

Hazard pictograms



		\checkmark
Signal word	:	Warning
Hazard statements	:	Flammable liquid and vapour.
Precautionary statements		
General	;	Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	:	Wear protective gloves. Wear eye or face protection. Keep away from heat, sparks, open flames and hot surfaces No smoking.
Response	:	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
Storage	:	Store in a well-ventilated place. Keep cool.
Disposal	1	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	:	Not applicable.
Supplemental label elements	1	Contains 2-butanone oxime. May produce an allergic reaction. Repeated exposure may cause skin dryness or cracking.
Special packaging requirem	en	<u>ts</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		

Other hazards which do : **P**rolonged or repeated contact may dry skin and cause irritation. not result in classification

SECTION 3: Composition/information on ingredients

Substance/mixture	: Mixture				
			Clas	ssification	
Product/ingredient name	Identifiers	%	67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	Туре
Naphtha (petroleum), hydrotreated heavy : Nota(s) P	EC: 265-150-3 CAS: 64742-48-9 Index: 649-327-00-6	>=20 - <25	R10 Xn; R65 R66	Flam. Liq. 3, H226 Asp. Tox. 1, H304	[1]
Naphtha (petroleum), hydrotreated heavy : Nota(s) P	REACH #: 01-2119457273-39 EC: 918-481-9 CAS: 64742-48-9 Index: 649-327-00-6	<10	Xn; R65 R66	Asp. Tox. 1, H304	[1]
2-butanone oxime	REACH #: 01-2119539477-28 EC: 202-496-6 CAS: 96-29-7 Index: 616-014-00-0	>=0.1 - <1	Carc. Cat. 3; R40 Xn; R21 Xi; R41 R43	Acute Tox. 4, H312 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351	[1]
English (GB)		United	l Kingdom (UK)		2/13

LEYLAND TRADE High Gloss		
Code : 00264606	Date of issue/Date of revision	: 31 January 2014

SECTION 3: Composition/information on ingredients

the full	text of the R- s declared section 16 for the s declared statements declared above.
----------	---------------------------------------------------------------------------------------------

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of mist ald m	icasules
Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

English (GB)	United Kingdom (UK)	3/13
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.	
	ediate medical attention and special treatment needed	
Ingestion	: No specific data.	
to control	irritation dryness cracking	
Skin contact	: Adverse symptoms may include the following:	
Inhalation	: No specific data.	
Eye contact	: No specific data.	
Over-exposure signs/sy	<u>mptoms</u>	
Ingestion	: No known significant effects or critical hazards.	
Skin contact	: Defatting to the skin. May cause skin dryness and irritation.	
Inhalation	: No known significant effects or critical hazards.	
Eye contact	: 📈 known significant effects or critical hazards.	
Potential acute health ef	fects	

Code : 00264606 LEYLAND TRADE High Gloss	Date of issue/Date of revision : 31 January 2014
SECTION 4: First aid	measures
Specific treatments	: No specific treatment.
SECTION 5: Firefigh	ting measures
5.1 Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
5.2 Special hazards arising f	om the substance or mixture
Hazards from the substance or mixture	: Fammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewe may create fire or explosion hazard.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
5.3 Advice for firefighters	
Special precautions for fire fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, prot	ective equipment and emergency procedures	
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.	
For emergency responders	: For non-emergency personnel".	
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).	
6.3 Methods and materials for	containment and cleaning up	
Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.	
English (GB)	United Kingdom (UK) 4/1	3

LEYLAND TRADE High Gloss		
Code : 00264606	Date of issue/Date of revision	: 31 January 2014

SECTION 6: Accidental release measures

Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

English (GB)	United Kingdom (UK)	5/13
7.3 Specific end use(s) Recommendations	: Not available.	
7.2 Conditions for safe storage, including any incompatibilities	: Storage temperature: 5 to 25°C (41 to 77°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original containe protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled contained Use appropriate containment to avoid environmental contamination.	1
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before ear drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.	ating,
	Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. T avoid the risks of fires, all contaminated materials should be stored in purpose-bu containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day be stored outside.	uilt and
Protective measures	: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before enter eating areas. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confine spaces unless adequately ventilated. Keep in the original container or an approv alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. I explosion-proof electrical (ventilating, lighting and material handling) equipment. non-sparking tools. Take precautionary measures against electrostatic discharge To avoid fire or explosion, dissipate static electricity during transfer by earthing an bonding containers and equipment before transferring material. Empty container retain product residue and can be hazardous. Do not reuse container.	and ing ed ed Use Use es. id

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (E	EU) No. 453/2010 -
United Kingdom (UK)	

Code : 00264606	Date of issue/Date of revision	: 31 January 2014	
LEYLAND TRADE High Gloss			

SECTION 7: Handling and storage

Industrial sector specific : Not available. solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs

DNELs - Not available.

PNECs

PNECs - Not available.

8.2 Exposure controls		
Appropriate engineering controls	:	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Individual protection measu	<u>res</u>	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Chemical splash goggles.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	:	

Code	: 00264606	Date of issue/Date of revision	: 31 January 2014
LEYLAND TR	ADE High Gloss		

SECTION 8: Exposure controls/personal protection

For prolonged or repeated handling, use the following type of gloves:

Recommended: nitrile rubber

Body protection	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

English (GB)		United Kingdom (UK)	7
Decomposition temperature	:	Not available.	
Auto-ignition temperature		Not available.	
Partition coefficient: n-octanol/ water	÷	Not available.	
Solubility(ies)		Insoluble in the following materials: cold water.	
Relative density		1.1	
Vapour pressure	:	Highest known value: 3.2 kPa (23.8 mm Hg) (at 20°C) (water). Weighted average: 1.41 kPa (10.58 mm Hg) (at 20°C)	
Upper/lower flammability or explosive limits	:	Lower: 0.49% Upper: 1.23%	
Flammability (solid, gas)	:	Not available.	
Material supports combustion.	:	Yes.	
Evaporation rate	:	Not available.	
Flash point	:	Closed cup: 39°C	
Initial boiling point and boiling range	1	145°C	
Melting point/freezing point	:	Not available.	
рН	:	Not available.	
Odour threshold	:	Not available.	
Odour	:	Hydrocarbon. [Slight]	
Colour	:	Various	
Physical state	:	Liquid.	
Appearance			
9.1 Information on basic physical	ar	nd chemical properties	

English (GB)

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 453/2010	-
United Kingdom (UK)	

Code : 00264606	Date of issue/Date of revision	: 31 January 2014
LEYLAND TRADE High Gloss		

SECTION 9: Physical and chemical properties

Viscosity	: 60 - 100 s (ISO 6mm)
Explosive properties	: Not available.
Oxidising properties	: Not available.

9.2 Other information

No additional information.

SECTION 10: Stabilit	and reactivity	
10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredier	nts.
10.2 Chemical stability	The product is stable.	
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur	·.
10.4 Conditions to avoid	When exposed to high temperatures may produce hazardous decomposition products.	
	Refer to protective measures listed in sections 7 and 8.	
10.5 Incompatible materials	Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.	
10.6 Hazardous decomposition products	Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.	9

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Naphtha (petroleum), hydrotreated heavy : Nota(s) P	LC50 Inhalation Vapour	Rat	8500 mg/m³	4 hours
	LD50 Oral	Rat	>6 g/kg	-
titanium dioxide	LD50 Oral	Rat	>10 g/kg	-
Naphtha (petroleum), hydrotreated heavy : Nota(s) P	LC50 Inhalation Vapour	Rat	8500 mg/m ³	4 hours
	LD50 Oral	Rat	>6 g/kg	-
2-butanone oxime	LD50 Oral	Rat	930 mg/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates

	Route		ATE value
Not available.			
Irritation/Corrosion			
Conclusion/Summary	: Not available.		
<u>Sensitiser</u>			
Conclusion/Summary	: Not available.		
Fraulish (OR)		l lucito d Kin e do no (l ll	0/40

```
English (GB)
```

Code : 00264606	Date of issue/Date of revision	: 31 January 2014
LEYLAND TRADE High Gloss		

SECTION 11: Toxicological information

<u>Mutagenicity</u>		
Conclusion/Summary	÷	Not available.
Carcinogenicity		
Conclusion/Summary	÷	Not available.
Reproductive toxicity		
Conclusion/Summary	\$	Not available.
<u>Teratogenicity</u>		
Conclusion/Summary	÷	Not available.
Specific target organ toxicity	(<u>single exposure)</u>
Not available.		

Specific target organ toxicity (repeated exposure) Not available.

Aspiration hazard

Product	/ing	redient name	Result
Maphtha (petroleum), hydroi Naphtha (petroleum), hydroi			ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1
Information on the likely routes of exposure	:	Not available.	
Potential acute health effect	: <u>ts</u>		
Inhalation	:	No known significant effects or cr	itical hazards.
Ingestion	:	No known significant effects or cr	itical hazards.
Skin contact	:	Defatting to the skin. May cause	skin dryness and irritation.
Eye contact	:	No known significant effects or cr	itical hazards.
Symptoms related to the pl	nysi	ical, chemical and toxicological	<u>characteristics</u>
Inhalation	:	No specific data.	
Ingestion	:	No specific data.	
Skin contact	:	Adverse symptoms may include t irritation dryness cracking	the following:
Eye contact	:	No specific data.	
Delayed and immediate eff Short term exposure	ects	and also chronic effects from s	<u>short and long term exposure</u>
Potential immediate effects	:	Not available.	
Potential delayed effects	:	Not available.	
Long term exposure Potential immediate effects	:	Not available.	
Potential delayed effects	:	Not available.	
Potential chronic health eff	ect	<u>s</u>	
Not available.			
Conclusion/Summary		Not available.	
General	:	Prolonged or repeated contact ca or dermatitis.	an defat the skin and lead to irritation, cracking and/
English (GB)		United Kingd	om (UK) 9/13

Code : 00264606	Date of issue/Date of revision	: 31 January 2014
LEYLAND TRADE High Gloss		

SECTION 11: Toxicological information

Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Other information	: Not available.

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 2-butanone oxime. May produce an allergic reaction.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
2-butanone oxime	Acute LC50 843000 to 914000 µg/l Fresh water	Fish - Pimephales promelas	96 hours

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
2-butanone oxime	0.63	5.01	low

12.4 Mobility in soil Soil/water partition coefficient (K _{oc})	: Not available.
Mobility	: Not available.
12.5 Results of PBT and vPv	B assessment
РВТ	: Not applicable.
vPvB	: Not applicable.
12.6 Other adverse effects	: No known significant effects or critical hazards.

```
English (GB)United Kingdom (UK)10/13
```

Code : 00264606	Date of issue/Date of revision	: 31 January 2014
LEYLAND TRADE High Gloss		

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

<u>Product</u>	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances

Packaging

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)	
Container	15 01 04	metallic packaging
Special precautions	taken when Empty conta residues ma container. I thoroughly i	al and its container must be disposed of in a safe way. Care should be handling emptied containers that have not been cleaned or rinsed out. ainers or liners may retain some product residues. Vapor from product ay create a highly flammable or explosive atmosphere inside the Do not cut, weld or grind used containers unless they have been cleaned nternally. Avoid dispersal of spilt material and runoff and contact with ays, drains and sewers.

14. Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3	3
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	No.	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

Additional information

ADR/RID

: This class 3 material can be considered non hazardous in packagings up to 450 L. Exempted according to 2.2.3.1.5 (Viscous substance exemption)

Code : 00264606 LEYLAND TRADE High Gloss	Date of issue/Date of revision	: 31 January 2014
14. Transport information		
Tunnel code : (D/E)		

i unnei code	: (D/E)
ADN	 This class 3 material can be considered non hazardous in packagings up to 450 L. Exempted according to 2.3.2.5 (Viscous substance exemption)
IMDG	 This class 3 material can be considered non hazardous in packagings up to 30 L. Exempted according to 2.3.2.5 (Viscous substance exemption)
IATA	: None identified.
Special precaut	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

the event of an accident or spillage.

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

VOC for Ready-for-Use Mixture : IIA/d. Interior/exterior trim and cladding paints for wood and metal. EU limit values: 300g/l (2010.)

This product contains a maximum of 300 g/l VOC.

Product/ingredient name	Carcinogenic effects	•	Developmental effects	Fertility effects
2-butanone oxime	Carc. 2, H351	-	-	-

15.2 Chemical Safety

: No Chemical Safety Assessment has been carried out.

Assessment

SECTION 16: Other information

Indicates information that has changed from previously issued version.
 Abbreviations and acronyms : ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

Code : 00264606 LEYLAND TRADE High Glos	Date of issue/Date of revision : 31 January 2014 s
SECTION 16: Other	information
Full text of abbreviated H statements	 H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H351 Suspected of causing cancer.
Full text of classifications [CLP/GHS]	: Acute Tox. 4, H312 Asp. Tox. 1, H304 Carc. 2, H351ACUTE TOXICITY (dermal) - Category 4 ASPIRATION HAZARD - Category 1 CARCINOGENICITY - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 FLAMMABLE LIQUIDS - Category 3 SKIN SENS. 1, H317: Acute Tox. 4, H312 ASPIRATION HAZARD - Category 1 CARCINOGENICITY - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Full text of abbreviated R phrases	 R10- Flammable. R40- Limited evidence of a carcinogenic effect. R21- Harmful in contact with skin. R65- Harmful: may cause lung damage if swallowed. R41- Risk of serious damage to eyes. R43- May cause sensitisation by skin contact. R66- Repeated exposure may cause skin dryness or cracking.
Full text of classifications [DSD/DPD]	: Carc. Cat. 3 - Carcinogen category 3 Xn - Harmful Xi - Irritant
<u>History</u>	
Date of issue/ Date of revision	: 31 January 2014
Date of previous issue	: 24 January 2014
Prepared by	: EHS
Version	: 13

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.