



# 722/723SERIES

## BOX SECTION EXTENSION LADDERS

**LIGHTWEIGHT  
& STRONG**



Box section stiles  
for maximum strength  
and minimum ladder  
weight



**IDEAL FOR JOBS AROUND THE WORK SITE**



Heavy duty stabiliser bar  
for added safety



'D' shaped rungs  
for comfort and security



Available in double  
and triple styles

# 150kg

MAX. LOAD  
(Load includes user, tools, materials, etc.)



- Box section stiles designed to ensure the ladder is lightweight but strong.
- Slip-resistant D rungs for comfort and security during use

### SPECIFICATIONS

Product Code	Section x Rungs	Closed Length	Open Length	Safe Working Height*	Weight
<b>DOUBLE SECTION</b>					
7221818 <sup>†</sup>	2 x 6	1.85m (6')	2.95m (9'8")	3.60m (11'9")	6.80kg
7222418	2 x 8	2.42m (7'11")	4.08m (13'4")	4.69m (15'4")	9.66kg
7222918	2 x 10	2.98m (9'9")	4.92m (16'1")	5.50m (18')	11.96kg
7223518	2 x 12	3.54m (11'7")	6.04m (19'9")	6.58m (21'7")	15.34kg
7224118	2 x 14	4.10m (13'5")	7.16m (23'5")	7.66m (25'1")	17.65kg
7224418	2 x 15	4.38m (14'4")	7.73m (25'4")	8.20m (26'10")	21.35kg
7224918	2 x 17	4.94m (16'2")	8.84m (29')	9.29m (30'5")	23.55kg

### TRIPLE SECTION

Compact ladders with a greater reach<sup>^</sup>

7231818	3 x 6	1.86m (6'1")	4.04m (13'3")	4.68m (15'4")	11.86kg
7232418	3 x 8	2.42m (7'11")	5.18m (17')	5.77m (18'11")	15.46kg
7232918	3 x 10	2.98m (9'9")	6.86m (22'6")	7.39m (24'3")	20.37kg
7233518	3 x 12	3.54m (11'7")	8.54m (28')	9.01m (29'6")	28.55kg
7234118	3 x 14	4.10m (13'5")	10.22m (33'6")	10.63m (34'10")	32.75kg

\*Based on 1.75m (5'9") as the average reach height of a person.

<sup>^</sup>Compared to a double section ladder with the same closed length.

<sup>†</sup>Stabiliser bar is not required or supplied with the double 1.85m model.



Nylon wheels for smooth ladder extension




Thumb operated locking catches prevent the sections separating, both in use and when being transported or stored

Heavy duty wide stabiliser with slip-resistant feet for added safety<sup>†</sup>



Robust box section stiles for strength and rigidity

Slip-resistant D rungs



EN131

Suitable for Professional & Non-professional use

