

TECHNICAL DATA SHEET

Date: 18/12/18
Version: 1001
Pages: 1

PVC Electrical Insulation Tape

DESCRIPTION

Self Adhesive Soft PVC Tape coated with a rubber based adhesive. Excellent conformability and good ageing characteristics. Lead free and BS3924.

APPLICATION

For splicing and wrapping electrical joints and terminations. Can also be used for colour coding, wrapping ducting and cable harnessing.

TECHNICAL

Thickness	0.13 mm
Adhesion to Steel	1.5 N/10 mm
Tensile Strength	25 N/10 mm
Adhesion to Backing	1.5 N/10 mm
Elongation at Break	151 %
Dielectric Strength	>40 KV/ mm
Max. Continuous Temp.	60°C
Flammability	Self Extinguishing to BS3924

Shelf life

12 months at 10 to 25°C storage conditions.

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Arc Building Products products' are available for sale in accordance with Arc Building Products standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our representatives, agents, or distributors, as the conditions of use, and any labour involved is beyond our control. Our warranty is therefore limited to the quality of supplied product.