

Contract Matt

Leyland Contract Matt is specially formulated to provide a full bodied, high opacity, matt finish to all interior walls and ceilings making it ideal for new work application.

Recommended uses

Interior ✓ Exterior ✗

Type of substrate

Plaster and embossed wallcoverings. Also suitable for use on wallboards, concrete, brickwork and blockwork.

Colour availability

Brilliant White and Magnolia (15ltr & 10ltr)

Finish

Matt

Volume solid

24%

Coverage

Leyland Contract Matt will cover approximately 13 square metres per litre depending on the nature and porosity of the surface. When using more than one tin of a colour in the same room, intermix before use.

Drying time

Recoat after 2-4 hours.

Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position. Protect from frost.

VOC content

MINIMAL VOC CONTENT 0-0.29% VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/a): 30g/l (2010). This product contains max 3g/l VOC.

Film thickness

Wet: 90µm

Dry: 22µm

Preparation

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime where required with Leyland Contract Primer Undercoat. Rub down glossy surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Seal absorbent surfaces with a solution of up to 1 part water to 9 parts Leyland Contract Matt.

Application

Stir well before use. Do not thin, except for absorbent surfaces, or when applying by roller or spray when a small quantity of clean water may be added. Suitable for application by brush, roller or spray. Apply paint evenly by brush or roller and avoid overspreading. If required, a second coat may be applied after 2 to 4 hours. Do not apply in temperatures below 10°C.

Cleaning

Remove as much product as possible from application equipment before washing. Replace lid firmly. Wash equipment immediately after use with warm soapy water. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

Warning

- Contains 1,2-benzisothiazol-3(2H)-one and 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.
- Safety data sheet available on request.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Do not breathe spray. Wear respiratory protection.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.