ISOVER ACOUSTIC-COMBI-ROLL

Declaration of Performance

Document No. IEINS108

Certificate No. 0003-CPR-21v1

Unique identification code of the product-type:

Acoustic Combi Roll See table here under.

Type, batch or serial number or any element allowing identification of the construction product as required under Article 11(4) of the CPR:

See product label

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Thermal Insulation for Buildings (ThIB)

Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Saint-Gobain Construction Products (IRL) Ltd. Registered in Ireland, Company No. 11815 Unit 4 Kilcarbery Business park, Nangor Road, Dublin 22; D22 R2Y7, Tel: +353 (0) 1 629 8400 Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

N/A

System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 1 (Reaction to fire)
System 3 (all other declared properties)

In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Notified certification body Element Materials Technology Rotterdam B.V. No. 2812 performed, carried out the determination of the product type, the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of constancy of performance (2812-CPR-BA0053) for Reaction to fire.





Declared performance table: According to EN13162: 2012+A1:2015

| Essential Characteristics | Performance | Abbrev. | Unit | Declared Performance | | |
|---|---|---------------------------|-----------|----------------------|-------|-------|
| Product Name | | | | Acoustic Roll (IE) | | |
| Reaction to fire | Reaction to fire | RtF | Euroclass | A1 | | |
| Release of dangerous substances to the indoor enviroment | Release of dangerous substances (e) | | | NPD | | |
| Acoustic absorption index | Sound absorption | | | NPD | | |
| Impact noise transmission index | Dynamic stiffness | | | NPD | | |
| | Thickness | d _i | | NPD | | |
| | Compressibility | С | | NPD | | |
| | Air flow resistivity | AF, | | NPD | | |
| Direct airbourne sound insulation index | Air flow resistivity | AF _r | | NPD | | |
| Continuous glowing combustion | Continuous glowing combustion (e) | | | NPD | | |
| Thermal resistance | Thermal resistance | $R_{_{D}}$ | m² K/W | 2.75 | 4.15 | 5.55 |
| | Thermal conductivity | $\lambda_{_{\mathrm{D}}}$ | W/m K | 0.036 | 0.036 | 0.036 |
| | Thickness | d _N | mm | 100 | 150 | 200 |
| | Thickness class | T _i | | T1 | T1 | T1 |
| Water permeability | Short term water absorption | W _p | kg/m² | NPD | | |
| | Long term water absorption | W _{lp} | | NPD | | |
| Water vapour permeability | Water vapour transmission | t or Z | | NPD | | |
| Compressive strength | Compressive stress or compressive strength | CS | | NPD | | |
| | Point load | F _p | | NPD | | |
| Durability of reaction to fire against heat, weathering, ageing/ degradation | Durability characteristics (a) | | Euroclass | A1 | | |
| Durability of thermal resistance against heat, weathering, ageing/ degradation | Thermal resistance (b) | R _D | m² K/W | 2.75 | 4.15 | 5.55 |
| | Thermal conductivity (b) | $\lambda_{_{\mathrm{D}}}$ | W/m K | 0.036 | 0.036 | 0.036 |
| | Durability characteristics (c) | d | | NPD | NPD | NPD |
| Tensile/fluxural strength | Tensile strength perpendicular to faces (d) | TR | | NPD | | |
| Durability of compressive strength against heat, weathering, ageing/ degradation | Compressive Creep | Xct, Xt | | NPD | | |

NPD No Performance Determined

(a) No change in Reaction to fire properties for mineral wool products.

The fire performance of mineral wool does not deteriorate with time.

The Euroclass classification of the product is related to the organic content, which cannot increase with time.

- (b) Thermal conductivity of mineral wool products does not change with time.
- (c) For dimensional stability thickness only.
- (d) This characteristic also covers handling and installation.
- (e) European test methods are under development.





The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Padraig Barry, Managing Director,

Saint-Gobain Construction Products (Irl) Limited

October 2021

CONTACT DETAILS FOR FURTHER INFORMATION:

Please visit our website at: www.isover.ie

Contact details:

Free Phone (ROI): **1800 744480**Free Phone (NI): **0845 3990159**Email: **tech.ie@saint-gobain.com**

ISOVER is part of the Saint-Gobain group, leader in the design, production and distribution of materials for construction, industrial and consumer markets. ISOVER is the specialist in insulation within the group.

Saint-Gobain Construction Products (Irl) Limited reserves the right to revise product specifications without notice. The information in this document was correct to the best of our knowledge at the time of publication. It is the user's responsibility to ensure that it remains current prior to use. The information in this document is for guidance only and should not be read in isolation. Users should read and familiarise themselves with all the information contained in this document and ensure that they are fully conversant with the products and systems being used, before subsequent specification or installation.



