



FINSA
solutions in wood

FINANCIERA MADERERA S.A. (FINSA)
N-550, KM 57
15890 SANTIAGO DE COMPOSTELA (A CORUÑA)
SPAIN

DECLARATION OF PERFORMANCE N° 00114



FIBRAPAN				
Manufactured at: Finsa Fibranor Polig. Ind. de Rábade 27370 RÁBADE (ESPAÑA)	Manufactured at: Finsa Orember Polig. Ind. San Cibrao das Viñas 32911 OURENSE (ESPAÑA)	Manufactured at: Finsa Padrón Paraíso s/n 15900 PADRÓN (ESPAÑA)	Manufactured at: Luso Finsa Estrada Nacional 234, Km 92.7 3524-952 NELAS (PORTUGAL)	Manufactured at: Finsa France SAS 151, Route de Hourés 40110 MORCENX (FRANCE)
PRODUCT TYPE	INTENDED USE	AVCP*		
MDF	Internal use as non structural component in dry conditions	4		

*Assessment and verification of constancy of performance system according to Annex V of regulation (EU) No 305/2011

TECHNICAL DATA-AVERAGE VALUES			Rev: 05/29/2018			
PROPERTIES	TEST METHOD	UNITS	THICKNESSES mm			
			7/9	>9/12	>12/19	>19/30
DENSITY (*)	EN 323	kg/m ³	770/740	735/720	720/675	675/655
INTERNAL BOND	EN 319	N/mm ²	0,75	0,65	0,55	0,55
BENDING STRENGTH	EN 310	N/mm ²	23	22	20	18
MODULUS OF ELASTICITY	EN 310	N/mm ²	2700	2500	2200	2100
THICKNESS SWELLING 24 H	EN 317	%	17	15	12	10
DIMENSIONAL MOVEMENT LENGTH/WIDTH	EN 318	%	0,4	0,4	0,4	0,3
DIMENSIONAL MOVEMENT TICKNESS	EN 318	%	6	6	6	5
SURFACE SOUNDNESS	EN 311	N/mm ²	1,2	1,2	1,2	1,2
SURFACE ABSORPTION (TWO FACES)	EN 382-1	mm	> 150	> 150	> 150	> 150
MOISTURE CONTENT	EN 322	%	7+/-3	7+/-3	7+/-3	7+/-3
GRIT CONTENT	ISO 3340	% Weight	≤ 0,05	≤ 0,05	≤ 0,05	≤ 0,05
FORMALDEHYDE CONTENT	EN ISO 12460-5	mg/100 g	≤ 8	≤ 8	≤ 8	≤ 8
REACTION TO FIRE TABLA EN 13986:2004+A1:2015 I	EN 13501-1	Class	E	D-s2,d0(**)	D-s2,d0(***)	D-s2,d0
SOUND ABSORPTION COEFFICIENT (A) (250 A 500 HZ)	EN 13984:2004+A1:2015	α	0.10	0.10	0.10	0.10
SOUND ABSORPTION COEFFICIENT (A) (1000 A 2000 HZ)	EN 13984:2004+A1:2015	α	0.20	0.20	0.20	0.20
THERMAL CONDUCTIVITY	EN 13984:2004+A1:2015	W/ (m·K)	0.13	0.13	0.12	0.12
AIRBORNE SOUND INSULATION (SURFACE MASS) (R)	EN 13986:2004+A1:2015	db	22/24	24/26	26/28	29/30
WATER VAPOUR PERMEABILITY DRY CUP	EN 13986:2004+A1:2015	μ	28	/27	25	/24
WATER VAPOUR PERMEABILITY WET CUP	EN 13986:2004+A1:2015	μ	18	17	16	15
BIOLOGICAL DURABILITY USE	EN 13986:2004+A1:2015	Class of use	1	1	1	1
CONTENT OF PENTACHLOROPHENOL (PCP)	EN 13986:2004+A1:2015	%	<5	<5	<5	<5

(*) VALUES TO BE CONSIDERED AS A ROUGH GUIDE ONLY.

(**) Mounted without an air gap behind the FIBRAPAN.
Mounted with a closed air gap not more than 22 mm behind the FIBRAPAN classification D-s2,d2.
Classification E for any other more restrictive condition. Commission Decision 2007/348/EC.

(***) Mounted without an air gap behind the FIBRAPAN, or with a closed air gap behind the FIBRAPAN for thicknesses equal or greater than 15mm or with an open air gap behind the FIBRAPAN for thicknesses equal or greater than 18 mm.
Mounted with a closed air gap not more than 22 mm behind the FIBRAPAN classification D-s2,d2 in thicknesses between 10 and 18 mm. Commission Decision 2007/348/EC.

These physical-mechanical values improve/comply with those established by EN 622-5:2009 European Standard, Table 3. Requirements for general purpose boards for use in dry conditions (type MDF).

FIBRAPAN meets Class E1 requirements (analysed according to EN ISO 12460-5) as defined in EN 622-1:2003 European Standard.

FIBRAPAN is endorsed by AITIM Quality Labels.

FIBRAPAN STRIP meets these physical-mechanical characteristics declared.

The performance of the reference product are in compliance with the performance declared above
This Declaration of Performance is issued under the sole responsibility of FINANCIERA MADERERA S.A. (FINSA)

Javier Portela
FINSA R&D + Quality Director
Santiago de Compostela 10/26/2018

