

FULMETAL REDIROLL

With a design life in excess of 30 years, Protect Fulmetal RediRoll sets the standard for dry fix ventilated ridge and hip systems.



Innovative, all aluminium construction

RediRoll, manufactured entirely from aluminium, stands above all other competitive systems. Exploiting the properties of aluminium gives Fulmetal RediRoll truly market leading performance.

Quick and easy to install, no ridge unions

Because aluminium is 'rot proof' RediRoll has no need for cumbersome plastic ridge unions to seal the gaps between the ridge tiles. These unions are often difficult to fit, add unnecessary time to any installation and fade over time through UV ageing. With noticeably fewer components RediRoll is a winner when it comes to ease of installation.

Truly universal

RediRoll fits the majority of ridges and hips - it is truly universal. It can also be used on mono ridges.

Better ventilation performance

With its innovative, no union design, RediRoll promotes a completely uninterrupted air flow. A ventilated dry ridge system has to move the equivalent of 5,000mm²/m of air, no problem for RediRoll.

AA fire rating

The advantages of aluminium keep on coming! Because it does not burn, Fulmetal RediRoll is AA fire rated enabling unrestricted use.



BENEFITS

- Conforms to Dry Fix Standard BS 8612.
- All aluminium construction.
- True 5,000mm²/m ventilation.
- Quick and easy to install - no ridge unions.
- Hooded ventilation design prevents water ingress.
- Universal - fits most ridges and hips.
- Stainless steel clips provide mechanical fix and even ridge tile spacing.
- Screw sleeve to prevent light bleed between ridges (if required).
- 6 metre length - ideal for most applications.
- Available in terracotta or grey.
- AA fire rated.
- Design life in excess of 30 years.
- Optional hip tile carrier also available.



Specification clause

Mechanically-fixed ventilated ridge and hip system to be Fulmetal RediRoll supplied by Protect Membranes, 2 Brooklands Road, Sale, Cheshire, M33 3SS. Tel: 0161 905 5700. Fax: 0161 905 2085. Email: info@protectmembranes.com. Dry fix system to provide high level roof ventilation and ensure mechanical fixing of ridge and hip tiles to BS 8612. Fixing system to be universal to suit any tile type on both ridges and hips, including mono ridge. To be continually installed to provide ventilation area equivalent to 5000mm²/m* to comply with Building Regulations Approved Document C2 and BS 5250. System to be fixed in accordance with manufacturer's instructions.

* For plain wing angle ridges, please consult Protect's Technical team.

Stockist's stamp



PROTECT MEMBRANES

2 Brooklands Road, Sale, Cheshire M33 3SS

Tel: 0161-905 5700 Fax: 0161-905 2085

Email: info@protectmembranes.com Web: www.protectmembranes.com

Protect Membranes maintains a policy of continuous development and reserves the right to amend product specifications without notice.



A division of Building Product Design Ltd. Company Registration No: 3944123

