Mayfair Flags

vibrant granite appearance

- Manufactured with natural granite aggregates
- Superb hard-wearing granite surface
- Vibrant long-lasting colours
- Creates a striking, contemporary look











product specifications

Product type	Concrete Pa	aving Fla	g		Concrete Paving Flag								
Manufactured to		BS EN 1339:2003											
Surface layer		Hard wearing surface layer with a minimum of 4mm and >390kgs/m³ cement											
Granite content	layer for Silv 46% of gran Sandstone;	Not less than 57% of granite aggregate in surface layer for Silver, Graphite and Russet; Not less than 46% of granite aggregate in surface layer for Sandstone; Not less than 32% of granite aggregate in surface layer for Rose											
Efflorescence		Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence											
Strength		Less than 50mm deep >3.5MPa Greater than 50mm deep >5MPa (Class 3)											
Slip/Skid risk	Extremely L	Extremely Low											
Installed to	BS 7533-4:	BS 7533-4:2006											
กรร	Plus: Q25 3	Plus: Q25 315 Create: 45-20-64/395											
Applications	sub-base de	Refer to the relevant part of BS 7533 for the correct sub-base design and the most suitable product size for your application. Available from www.bsigroup.com											
Energy used	100% renev	100% renewable energy											
Water used		100% from our rainwater harvesting system and groundwater bore hole											
Recycled content	Not less tha	ın 6%											
Carbon Footprint		35mm	40mm	50mm	65mm	70mm							
* kgCo²e/m²	Silver Sandstone Graphite Russet Rose	14* 15* 15*	16* 17* 17* 17* 17*	19* 22* 24* 22* 22*	24* 28* 30*	30* 32* 32*							
Recyclable	100% of thi	100% of this product can be recycled											
Manufacturing & Delivery	From one lo	From one location within the UK											
breeam rating www.bre.co.uk	A , according to the Green Guide to Specification, 4 th Edition 2009. A+ , can be achieved by using a recycled												

Tobermore products are manufactured in accordance with an accredited ISO 9001:2015 quality system. Manufacturing facilities are accredited to ISO14001:2015 Environmental Management. The company publish environmental labels and declarations in accordance with BS EN ISO 14021:2016 and BES 6001.





sub-base.





colours













product	size (mm)	finish	edge	colours available	in stock	no. per m²	no. per pack	weight (kg) per pack
MAYFAIR FLAGS BIM	600 x 600 x 50	GRANITE TEXTURED	CHAMFERED	Graphite, Sandstone, Silver	YES	2.78	20	859
	600 x 400 x 50	GRANITE TEXTURED	CHAMFERED	Graphite, Sandstone, Silver	YES	4.16	20	589
				Rose, Russet	SPECIAL ORDER			
	450 x 450 x 70	GRANITE TEXTURED	CHAMFERED	Graphite, Sandstone, Silver	YES	4.94	15	512
	450 x 450 x 50	GRANITE TEXTURED	CHAMFERED	Graphite, Sandstone, Silver	YES	4.94	20	470
	450 x 450 x 35	GRANITE TEXTURED	CHAMFERED	Graphite, Sandstone, Silver	YES	4.94	30	529
	400 x 400 x 40	GRANITE TEXTURED	CHAMFERED	Graphite, Sandstone, Silver, Rose, Russet	YES	6.25	25	384
	400 x 400 x 65	GRANITE TEXTURED	CHAMFERED	Graphite, Silver	YES	6.25	16	395
				Sandstone	MADE TO ORDER			

BIM This product is available to download from our website in BIM Level 2 format.

Refer to all instructions and warnings on our website