

Product Description

Lignum Strata Fourteen/3
Engineered Wooden Flooring

| Property | Information |
|------------|---|
| Dimension | 400-1500 x 127 x 14 mm Top layer > 3.0 mm |
| Packing | Pack quantity = 2.794m ² 52 cartons per pallet = 142.288m ² |
| Production | Multi-ply construction |
| Laying | Tongue & groove Can be laid as floating floor, stuck down or nailed (see instructions) |

Product Specification HDF Core

| Factor | Standard | Comments |
|------------------------------------|----------|--|
| Resistance to roller castor chairs | EN 425 | Use of conventional chairmat recommended |
| Effect of furniture legs | EN 424 | No visible change |
| Thermal conductivity | EN 12664 | 0.077 m ² K/W |
| Formaldehyde | EN 717-1 | ≤ 0.05 ppm |
| Disposal | | Private waste disposal with regular household waste acceptable |
| Suitability for underfloor heating | | Suitable up to 27°C |

Product Specification Laminated Floorboards

| | | |
|---------------------|------------|-----------------|
| Slip resistance | EN 13893 | $\mu \geq 0.47$ |
| Resistance to fire | EN 13501-1 | D s1 |
| Chemical resistance | EN 13442 | Category 5 |

Wood Innovations 9 Springhill Road, Newry, County Down, N. Ireland. BT35 6EF

Tel: 028 4177 3366

Email: sales@woodinnovations.co.uk

www.woodinnovations.com