



THE WORLD LEADER IN LADDERS™



Fibreglass Trade Swingback Stepladder

716SERIES

The best overall choice for any trade



Fibreglass Stiles

- Strong and durable
- High visibility colour
- Non-conductive stiles, ideal for working around electricity



Holster Top

- Holds tools and supplies
- Saves trips up the ladder
- Lock-in accessories



EDGE Brace System

- Provides enhanced strength and protection against damage

IMPROVED DESIGN

Visit us online to see our full line of ladders

www.midlandladders.com

LOCK-IN ACCESSORY SYSTEM



Lets you customise the ladder top and safely secure your tools



THE WORLD LEADER IN LADDERS™

716SERIES


Fibreglass Trade Swingback Stepladder

150kg
MAX. LOAD
(Load includes user, tools, materials, etc)




Holster Top with specially designed tool and equipment holders


Non-conductive fibreglass stiles, ideal for working around electricity




Heavy duty slip-resistant tread profile for added strength and security



EDGE moulded brace and foot pad combination provides enhanced bracing strength and protects the base tread from damage




Semi-tubular rivets provide rigid fixings



H-spreaders to enable single handed operation and add to the strength and stability of the ladder

Generous 298mm tread pitch gives excellent working heights



EN131

Suitable for Professional & Non-professional use

SPECIFICATIONS

Product Code	No. of Treads	Max. Standing Height	Safe Working Height*	Weight
7160418	4	0.29m (11")	2.04m (6'8")	6.79kg
7160518	5	0.56m (1'10")	2.32m (7'7")	7.70kg
7160618	6	0.84m (2'9")	2.59m (8'6")	8.80kg
7160818	8	1.40m (4'7")	3.15m (10'4")	11.60kg
7161018	10	1.95m (6'4")	3.70m (12'2")	16.50kg
7161218	12	2.51m (8'2")	4.26m (13'12")	19.60kg

*Based on 1.75m (5'9") as the average reach height of a person.



APPROVED TO THE
NEW EN131 STANDARD
FOR PROFESSIONAL USE

FIBREGLASS

For working around electricity
Non-conductive stiles