

Country Stone

natural, nostalgic style

- Emulates natural stone
- Vibrant long-lasting colours
- Creates a classic, vintage look

product specifications

Product type	Concrete Block
Manufactured to	BS EN 771-5:2011
Efflorescence	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence
Strength	Typical tensile splitting strength of >20N/mm ² mean
Installed to	BS 5628-3:2005
Shrinkage (Moisture movement)	0.41mm/m
Durability (Freeze/Thaw)	F2 (Severe exposure)
Tolerances	D1
Reaction to fire	A1
Water absorption by capillary	3 g/(m ² x s)
Water absorption	<7% water absorption on average
Water vapour diffusion coefficient	30/100 μ
Net dry density	2210 kg/m ³
Gross dry density	2200 kg/m ³
Shear bond strength	0.15N/mm ²
Thermal conductivity	Protected 1.25W/m K Exposed 1.43W/m K
Mortars & Expansion Joints	BS 5628-3:2005
Bed Reinforcement	BS 5628-3:2005
BS	Plus: F10 295 Create: 45-80-50/322
Applications	Above ground, main external wall construction, boundary walls, columns and partitions.
Energy used	100% renewable energy
Water used	100% from our rainwater harvesting system and groundwater bore hole
Recycled content	Not less than 5%
Carbon Footprint	36kgCo ₂ e/m ²
Recyclable	100% of this product can be recycled
Manufacturing & Delivery	From one location within the UK
breedm rating www.bre.co.uk	A+ , according to the Green Guide to Specification, 4 th Edition 2009.

Tobermore products are manufactured in accordance with an accredited ISO 9001:2015 quality system. Manufacturing facilities are accredited to ISO14001:2015 Environmental Management. The company publish environmental labels and declarations in accordance with BS EN ISO 14021:2016 and BES 6001.

colours



product	size (mm)	colours available	in stock	m ² per pack	m ² per slice	no. per pack	weight (kg) per pack
COUNTRY STONE (single course mixed length) (all sizes in one pack)	375 x 100 x 140	Bracken, Buff, Heather, Slate	YES	6.72	1.34	40	1560
	225 x 100 x 140	Cedar, Natural	SPECIAL ORDER			40	
	160 x 100 x 140					40	
	240 x 100 x 140					40	
	200 x 100 x 140					40	
COUNTRY STONE BIM (single sizes)	375 x 100 x 65	Bracken, Buff, Slate	YES	6.44	0.59	264	1460
	300 x 100 x 65	Cedar, Heather, Natural	SPECIAL ORDER	6.86	0.62	352	1540
		Bracken, Buff, Slate	YES				
	225 x 100 x 65	Cedar, Heather, Natural	SPECIAL ORDER	5.15	0.47	352	1150
		Bracken, Buff, Slate	YES				
	375 x 100 x 140	Cedar, Heather, Natural	SPECIAL ORDER	6.3	1.26	120	1456
		Bracken, Buff, Slate	YES				
	300 x 100 x 140	Cedar, Heather, Natural	SPECIAL ORDER	6.72	1.34	160	1546
		Bracken, Buff, Slate	YES				
	225 x 100 x 140	Cedar, Heather, Natural	SPECIAL ORDER	5.04	1.01	160	1147
		Bracken, Buff, Slate	YES				
	440 x 100 x 215	Cedar, Heather, Natural	SPECIAL ORDER	6.05	1.51	64	1357
		Bracken, Buff, Slate	YES				
300 x 100 x 215	Cedar, Heather, Natural	SPECIAL ORDER	6.19	2.06	96	1428	
	Bracken, Buff, Slate	YES					
COUNTRY STONE COPING	208 x 300 x 80	Bracken, Buff, Heather, Slate	YES	-	-	128	1416
		Cedar, Natural	SPECIAL ORDER				

BIM This product is available to download from our website in **BIM Level 2** format.

Refer to all instructions and warnings on our website

visit www.tobermore.co.uk | call us **028 7964 2411** (ROI replace 028 with 048) | follow us [f](#) [t](#) [i](#) [in](#)

02G18