

Beaufort Flags

contoured stone appearance

- Superb hard-wearing surface
- Natural, muted colour range
- Resembles the aesthetics of natural stone
- Contemporary appearance

product specifications

Product type	Concrete Paving Flag
Manufactured to	BS EN 1339:2003
Surface layer	Hard wearing surface layer with a minimum of 4mm and >390kg/m ³ cement
Efflorescence	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence
Strength	Less than 50mm deep >3.5MPa Greater than 50mm deep >5MPa (Class 3)
Slip/Skid risk	Extremely Low
Installed to	BS 7533-4:2006
BS	Plus: Q25 315 Create: 45-20-64/395
Applications	Refer to the relevant part of BS 7533 for the correct sub-base design and the most suitable product size for your application. Available from www.bsigroup.com
Energy used	100% renewable energy
Water used	100% from our rainwater harvesting system and groundwater bore hole
Recycled content	Not less than 5%
Carbon Footprint	400x400x40mm: 18kgCo ² e/m ² 600x400x40mm: 17kgCo ² e/m ²
Recyclable	100% of this product can be recycled
Manufacturing & Delivery	From one location within the UK
breem rating www.bre.co.uk	A , according to the Green Guide to Specification, 4 th Edition 2009. A+ , can be achieved by using a recycled sub-base.

Tobermore products are manufactured in accordance with an accredited ISO 9001:2015 quality system. Manufacturing facilities are accredited to ISO14001:2015 Environmental Management. The company publish environmental labels and declarations in accordance with BS EN ISO 14021:2016.

colours



FM 11763 EMS 88400

product	size (mm)	finish	edge	colours available	in stock	no. per m ²	no. per pack	weight (kg) per pack
BEAUFORT FLAGS	400 x 400 x 40	CONTOURED	CHAMFERED	Buff, Charcoal, Natural	YES	6.25	25	403
	600 x 400 x 40	CONTOURED	CHAMFERED	Buff, Charcoal, Natural	YES	4.16	25	569

Refer to all instructions and warnings on our website