

**TEGRAL RIVENDALE SLATES**  
**Product Data Sheet**



Tegral Rivendale slates are designed to reflect the qualities of natural slate, at a fraction of the cost. They are available in blue black or heather. Rivendale slates have a beautifully textured surface and dressed edges, combining the benefit of modern slate technology with the look of a natural slate. They come with a 20 year colour guarantee and a 30 year structural guarantee, giving you complete peace of mind.

<b>TECHNICAL DATA</b>	
Size of slate	600mm x 300mm
Minimum pitch	25° (110mm headlap)
Maximum pitch	90°
Typical laps	100, 110mm
Batten gauge	245-250mm
Slate thickness	4mm
Covering capacity (net)	13.4 slates/m <sup>2</sup> (100mm headlap) 13.6 slates/m <sup>2</sup> (110mm headlap)
Weight of slating (approx.)	20.4 kg/m <sup>2</sup> (0.20 kN/m <sup>2</sup> ) at 100mm headlap 20.9 kg/m <sup>2</sup> (0.20 kN/m <sup>2</sup> ) at 110mm headlap
Batten required (net)	4.00 (net lin.m/m <sup>2</sup> ) at 100mm headlap
Batten size recommended (fixed to SR82)	50 x 25mm for rafters/supports not exceeding 400mm centres 50 x 35mm for rafters/supports not exceeding 600mm centres
Fixings	Slate nails (30 x 2.65mm) Copper disc rivets (19mm dia. x 2mm stem)
Authority	EN 492
Colours available	Blue Black, Heather

**Specification:**

Tegral Rivendale slates are manufactured to EN492, Type NT, 4.0mm thick Fibre Cement Slates in Ireland, with a nominal density of 1970kg/m<sup>3</sup>. Rivendale slates have a textured surface with a dressed edge and are offered with a 20 year manufacturer’s colour guarantee due to Tegral’s siliconised painting process and a 30 year structural guarantee. Tegral Building Products is independently certified as meeting requirements of ISO 9001(quality), ISO 14001 (environment), OHSAS 18001 (safety) and BES 6001 (responsible sourcing).

**Sustainability:**

Green guide rating	A+ (Element ref: 812410008)
BES 6001	Rated “Excellent” – can achieve three credits
EPD	Available for Rivendale Slates

For further information visit [www.tegral.com](http://www.tegral.com), call +353 (0)59 863 1316 or email our technical support department on [support@tegral.com](mailto:support@tegral.com)

Full properties and performance information for Rivendale slates is available for download on our website in the [resources section](#).